

BRUSHED ALUMINUM KEY SWITCHES



Fits std. single gang boxes.



Mullion style. Only 1 3/4" wide. (LED optional)

CM1120

CM2020

Cylinders Not Included


- Accept standard mortise cylinders 1" to 1 1/4"
- Heavy duty 1/4" thick aluminum plate
- 1 piece die cast construction
- Vandal resistant
- Tamper proof screws provided
- Indoor or outdoor applications
- UL/CSA approved switches
- 1 or 2 switches may be installed
- Wide range of switch configurations
- Color coded 18 AWG soldered leads
- Optional LED indicators
- Optional 1-60 second pneumatic time delay

P/N	Function	List
CDCM1120	SPDT momentary	84.00
CDCM2020	SPDT momentary	84.00

PUSH BUTTONS



Single gang



Narrow face-plate

CM30E
CM30EE

CM310EE

- 12/24V operation
- EE models incorporate an integrated 30 second timer with double break circuitry for additional safety.
- Stainless steel faceplates
- Optional LED's available

P/N	Function	List
CDCM30E	SPDT momentary	60.00
CDCM30EE	SPDT momentary	124.00
CDCM310EE	SPDT momentary	100.00

CM-60 Series - All-Active 6" Round Switch



- Rubber dampers for smoother actuation and quiet operation
- Durable stainless steel or solid brass construction
- All-Active design requires minimal actuation force
- Meets ADA requirements
- UL/CSA approved SPST N/O switch, rated 3 amps @ 120V AC
- Architectural finishes

CDCM60/4
112⁰⁰

CM-42 - Mounting Posts

- Supplied with acrylic cap and stainless steel mounting hardware
- Designed for use with RF controls
- Optional in-ground mounting base
- Clear aluminum, dark bronze, or mill finish
- Single gang cut-out is standard. No cut-out is also available. Single gang switch prep; fits: CM-35/40/41/45/46/60 series



CDCM42-CSU-CLR
Aluminum Finish
340⁰⁰

Switch Not included

CDCM42-CSU-BRZ
Dark Bronze Finish
340⁰⁰

CDCM42IG
Mounting Post
26⁰⁰

LIGHTED PIEZO EXIT BUTTONS

- Water & vandal resistant
- Rugged stainless steel face plate
- Red and/or green illumination
- Fail safe / non fail safe selectable
- N/O & N/C outputs
- 12/24V DC
- Integrated adjustable 40 sec. timer
- Lifetime Warranty



CDCM9600/7
160⁰⁰

CM-25 Series-All-Active Narrow Switch

- Mounts in aluminum jamb or in surface boxes
- Durable stainless steel or solid brass construction
- All-Active design requires minimal actuation force
- Meets ADA requirements
- UL/CSA approved SPST N/O switch, rated 3 amps @ 120V AC
- Architectural finishes



CDCM25/4
74⁰⁰

PIEZO EXIT SWITCH

- One piece aluminum construction
- No moving parts
- No power required to operate
- Solid state output (N/O)
- Virtually impervious to vandalism



CDCM9700/7
160⁰⁰

CM-40 Series - All-Active 4 1/2" Round Switch

- Rubber dampers for smoother actuation and quiet operation
- Durable stainless steel or solid brass construction
- All-Active design requires minimal actuation force
- Meets ADA requirements
- UL/CSA approved SPST N/O switch, rated 3 amps @ 120V AC
- Architectural finishes




CDCM40/4
110⁰⁰

CM-49 "SPACESHIP" ENCLOSURE

- CM-49A attaches to in-wall one gang, two gang, or 4 by 4 box
- CM-49B for surface mounting
- May be ordered as complete kit (for surface or flush mounting), or as individual components

Switch Not Included



CDCM49
54⁰⁰

ALL ACTIVE SWITCHES CM45 Series - All-Active - 4 1/2 Inch Square


- Large, easy to operate switches
- Round or square faceplates
- All-active design requires minimal actuation force
- Durable stainless steel or solid brass
- UL/CSA approved SPDT momentary, switch, rated 15 amps @ 125V AC
- Architectural finishes
- Various logos & messages



CDCM45/4
122⁰⁰

ABS Surface mount box for 4 1/2" square switches.

CDCM43CBL
28⁰⁰



MUSHROOM EXIT SWITCH

- 4 1/2" by 2 3/4" single gang stainless steel faceplate
- Rugged free-spinning button
- 10 amp contact



CDCM420E
84⁰⁰

MECHANICAL PUSH BUTTON



- 4 3/8" by 2 3/4" wide
- Indoor & outdoor applications
- Ideal for door jamb installation
- Heavy duty cast aluminum faceplate

CDCM9080
100⁰⁰

CX-1000/74 MICRO-MINDER




- Ultra compact design
- Adjustable delay from 1-30 seconds
- Color coded leads & plastic case
- 12-24V AC/DC
- SPDT contacts rated 3 amps @ 30V DC
- Dimensions: 1 1/4" x 2 1/4" x 3/4"

CDCX1000/74
28⁰⁰


CX-247 7 Day Timer

- 8 daily or weekly schedules
- Internal memory back-up
- Easy to program/ setup
- Extremely compact size
- H models feature "First-Man-In" function (holiday/snow day)
- 12 or 24V DC models
- SPDT contacts rated 16 amps @ 30V DC
- Dimensions: 2 3/8" x 2 3/8" x 1 1/4"



P/N	Function	List
CDCX247-12	12VDC	82.00
CDCX247-24	24VDC	82.00

CX-11PLUS R SWITCHING NETWORK



- Micro-processor controlled
- Independant wet/dry & interphone inputs
- Momentary or maintained user selectable operation
- LED's for visual confirmation
- Built in isolating relay
- 12-24V AC/DC
- 2 SPDT contacts rated 4 amps @ 30V DC
- DOR #1: .5 - 30 seconds
- DOR #2: .5-30 seconds
- Dimensions: 2 1/4" x 3 1/4" x 3/4"
- Latching relay toggles output #2 only

CDCXPLUS-R
126⁰⁰

CM-RX - RF Receivers

- 1 channel receiver, 10 code memory



- Ideal for varied commercial and handicap applications
- Form C relay output
- 15 second adjustable timer
- Push and learn technology
- 24V AC/DC

CDCMRX-7TD
100⁰⁰

CM-TX - RF Transmitters

- Ideal for varied commercial and handicap applications
- Single Channel
- Keychain size

CDCMTX-1M
46⁰⁰



CM-703 - Blue Pull Stations

- Available in English, French or bilingual
- Clear lift cover optional
- One N/O and one N/C switch



CDCM703
54⁰⁰

CM-419 Request-to-Exit Sensor

CDCM419W
126⁰⁰



- Passive infra-red sensor
- Dual pyros for increased stability
- Ceiling, wall or frame mount
- Adjustable coverage for single and double doors
- Adjustable .25-60 second timer
- 12-24 V AC/DC
- Two form C relay outputs for activating cameras, remote devices, door shunting or to de-activate mag lock in case of system failure
- Fail-safe or fail-secure operation
- U/L listed